

**application**    **Subgrade Reinforcement**  
**location**        **Sandia Creek, Temecula, California**  
**products**        **Geolon® HP570**

**THE CHALLENGE**

The water from the irrigation of the orange groves coupled with low lying areas bordering Sandia Creek Road caused major rutting and potholes. It was determined by the engineer that geosynthetic reinforcement would be needed to prevent future subgrade failure. The use of the geosynthetic would eliminate the need for over-excavation and reinforce sections where higher elevations were needed to allow proper drainage.

**THE DESIGN**

It was determined early on that a geosynthetic would be needed to construct a competent road. The use of Geolon® HP570 served two functions; reinforcement and separation. The high performance woven fabric separated the base material from the fine grained soils within the subgrade and increased the bearing capacity of the base material. Another reason for the use of Geolon® HP570 was that inclusion of culverts under the road. The concern

over settlement above these culverts prompted the use of a geosynthetic.

**CONSTRUCTION**

Placement of the geotextile was completed after the placing and levelling of the fill over the new culverts. An 8 in. lift of base material was bottom dumped and bladed level over the fabric. The ability to dump the base course directly on the Geolon® HP570 made it possible to construct the road using standard construction practices.

**PERFORMANCE**

Where questionable subgrades are encountered, geotextiles have been proven to be an economical solution in the construction of the project. The use of Geolon® HP570 allowed for decreased overexcavation in softer fill areas. All involved in the project are pleased with the results. Petra Geotechnical will be utilizing geosynthetics in other projects in the area after viewing this success.



Fill was dumped and levelled over the fabric.

Project is completed with positive results.



JOB OWNER:

**Sandia Creek, Santa Rosa  
Community Services District**

ENGINEER:

**Petra Geotechnical**

CONTRACTOR:

**Springer Excavating & Grading**



Geolon® HP570 is rolled out over the subgrade. HP570 serves two functions: to reinforce and separate.

The information contained herein is to the best of our knowledge accurate, but since the circumstances and conditions in which it may be used are beyond our control, we do not accept any liability for any loss or damage, however arising, which results directly or indirectly from use of this information nor do we offer any warranty or immunity against patent infringement.

365 South Holland Drive  
Pendergrass, GA 30567  
(888) 795-0808  
Fax (706) 693-4400

[www.tcnicolon.com](http://www.tcnicolon.com)



Ten Cate Nicolon